

# Technical Specification: Connection Units



## CATEGORY:

### SWITCHED FUSED CONNECTION UNITS

Insert Ref:

05/1	1 gang 13A Double Pole Fused Spur
05/2	1 gang 13A D/P Fused Spur+Neon
05/3	1 gang 13A D/P Fused Spur+Neon+ Cable Outlet

### I-GRID CABLE OUTLET MODULE

Insert Ref:

05/0	Cable Outlet Module
------	---------------------

### UNSWITCHED CONNECTION UNIT

Switched Poles:- None

Contact Gap Min:- None

Insert Ref:

05/4	1 gang 13A Fuse Only
------	----------------------

## TECHNICAL SPECIFICATION:

Current Rating:	13 Amp	Location:	Internal Use Only
Voltage:	220/250V AC	Max Installation Altitude	2000m
Max Load:	13 Amp		
IP Rating:	IP2XD	Standard Switch to Wood electrical accessories are	
Switched Poles: (05/1, 05/2, 05/3)	Double	designed to be mounted onto BS4662-2006 flush	
Contact Gap Minimum	3mm	wall boxes	
Product Class 1:	Must be earthed		
Ambient operating Temperature:	-5 to +40 C	BS EN ISO Standard	
Cable Outlet Size Flexible:	Min 0.75mm <sup>2</sup> Max 2.5mm <sup>2</sup>	Switched Fuse/Unswitched	BS 1363-4
		Fuse with Halo	BS 5733
Cable Outlets Fitted with Clamp:	Yes	Fuse with Halo + fuselink	B S 5733 and BS 1362
		Cable Outlet	BS 5733

	1mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm <sup>2</sup> Multi-Strand	6mm <sup>2</sup>
Switched /Fuse+Halo Terminal Capacity			3	2	1
Switched/Fuse+Halo Earth terminal Capacity	6	5	3	2	1
Cable Outlet Terminal Capacity	5	4	2	2	
Cable Outlet Terminal Capacity	6	5	3	2	1
FO/FOC Terminal Capacity	5	4	3	1	1
FO/FOC Earth Terminal Capacity	6	5	3	2	1

## Plate Fixing Centres:

Single Plate - 60.3mm    05/1, 05/2, 05/3, 05/4, 05/0