

Technical Specification:

Triple Pole Fan Isolator



CATEGORY:

Fan Isolator

Insert Ref:

03/1 1 gang 10A Triple Pole Rocker

TECHNICAL SPECIFICATION:

| | | | |
|--------------------------------|------------------|---|-------------------|
| Current Rating: | 10A | Location: | Internal Use Only |
| Voltage: | 220/250V AC | Max Installation Altitude | 2000m |
| IP Rating: | IP2XD | | |
| Max Load: | 10 Amp Resistive | | |
| Switched Poles: | Triple | Standard Switch to Wood electrical accessories are designed to be mounted onto BS4662-2006 flush wall boxes | |
| Contact Gap Minimum | 3mm | | |
| Product Class 1: | Must be earthed | | |
| Ambient operating Temperature: | -5 to +40 C | BS EN ISO Standard | BS EN 60669-1 |

| | 1mm ² | 1.5mm ² | 2.5mm ² | 4mm ² Multi-Strand | 6mm ² |
|-------------------------|------------------|--------------------|--------------------|----------------------------------|------------------|
| Terminal Capacity | 5 | 4 | 1 | 1 | 1 |
| Earth Terminal Capacity | 5 | 4 | 3 | 1 | 1 |

Plate Fixing Centres:

Single Plate - 60.3mm 03/1